



## Specifications

| MODELS  | VOLTS | WATTS | AMP  | LENGTH | WEIGHT |
|---------|-------|-------|------|--------|--------|
| HS-1208 | 120   | 800   | 6.7  | 35"    | 7 LBS  |
| RS-1208 | 120   | 800   | 6.7  | 35"    | 7 LBS  |
| HS-2408 | 240   | 800   | 3.4  | 35"    | 7 LBS  |
| RS-2408 | 240   | 800   | 3.4  | 35"    | 7 LBS  |
| HS-1215 | 120   | 1500  | 12.5 | 65"    | 11 LBS |
| RS-1215 | 120   | 1500  | 12.5 | 65"    | 11 LBS |
| HS-2420 | 240   | 2000  | 8.3  | 65"    | 11 LBS |
| RS-2420 | 240   | 2000  | 8.3  | 65"    | 11 LBS |

## Temperature Rise and Heat Pattern

| Height Above Subject | 800W Temp Rise | 800W Heat Pattern | 1500 W Temp Rise | 1500W Heat Pattern | 2000W Temp Rise | 2000W Heat Pattern |
|----------------------|----------------|-------------------|------------------|--------------------|-----------------|--------------------|
| 2 FT                 | 83 DEG F       | 4.5 X 4.5 FT      | 108 DEG F        | 7 X 4.5 FT         | 125 DEG F       | 7 X 4.5 FT         |
| 3 FT                 | 49 DEG F       | 5 X 7 FT          | 70 DEG F         | 7.5 X 7 FT         | 75 DEG F        | 7.5 X 7 FT         |
| 4 FT                 | 37 DEG F       | 5.5 X 9.5 FT      | 51 DEG F         | 8 X 9.5 FT         | 55 DEG F        | 8 X 9.5 FT         |